



TECHNICAL BULLETIN

BLUSEAL

ELASTOMERIC SEALANT

CODE NUMBER

DP-706

DESCRIPTION

This is a water-based elastomeric sealant for sealing cracks and leaks on concrete walls and floors, leaks on G.I. Sheet and Masonry Tile roofs, on concrete and G.I Sheet gutters, flashings, downspouts, nailholes and plumbing leaks. It is environment-friendly and does not contain any harmful components. It is very easy to apply, by putty knife or even brush. It is weatherproof and does not become brittle, chalk or crack upon exposure to sunlight. It may be painted over. It only needs to be applied in thin coats. It is a handy item to have on hand in every home, shop, factory, warehouse, etc. in anticipation of leaks that may occur, particularly during rainy season. It will adhere well to G.I. sheet or pipe, PVC, wood and masonry. Lead free, lacquer free and especially formulated for clean environment.

COLOR

Gray in 4 kilogram, 1 kilogram, 500 gram and 250 gram plastic container.
Red, green, blue, beige, gray and white in 100 gram sachet.

FINISH/ SHEEN

Flat.

SURFACES TO BE PAINTED, SUBSTRATES

Concrete, ceramic and other masonry. G.I sheets and other metals. PVC and other plastics. Wood. Surfaces are preferred dry. However, it may be applied on wet surfaces provided there is no flow of water or no sprinkling or dropping or pouring of rain or tap water, during application and during drying. There should also be water pressure such as pressure coming from a pipe even after the sealant is dry.

THINNER/ REDUCER

Use as-is.

TINTING COLOR

Not applicable.

APPLICATION

Apply by putty knife or brush.

COVERAGE/ SPREADING RATE

Depends on thickness applied.

DRYING TIME

One (1) hour.

MIXING INSTRUCTIONS

Use as-is.

PACKAGING

Available in 4 kilogram, 1 kilogram, 500 gram, 250 gram plastic container and 100 gram sachets.
Colors in 100 gram sachet: gray, red, green, blue, beige and white.

CAUTIONS

1. Store in shaded ventilated area.
2. Keep out of reach of children.
3. Keep tightly closed when not in use.

(10/15/11)