



TECHNICAL BULLETIN

ZERO RUST CONVERTER

CODE NUMBER

DP-1002

DESCRIPTION

The most convenient formula for the removal of rust from ferrous metal. No home, no factory, no shop, no ship should be without it. Simply apply it over the rusted surface and watch the rust go away. Converts rust to another substance that is easier to remove. Works immediately upon application. Convenient for applying on roofs, gates and other metal parts of homes, at the first sign of rust, so as not to allow it to spread. For industrial uses, just apply and let it dry overnight. It leaves a chemically bonded phosphate coating that will protect the metal from corrosion until the application of metal primer.

COLOR

Clear.

FINISH/ SHEEN

Rust particles turn to grayish-black upon completion of reaction.

SURFACES TO BE PAINTED, SUBSTRATES

Ferrous metals – steel, iron and some stainless steels. For domestic, industrial and marine applications.

THINNER/ REDUCER

Use as-is.

TINTING COLOR

Not applicable. Do not tint.

APPLICATION

Brush, roller or rag.
Acidic solution. Take all precautions as against acids.

COVERAGE/ SPREADING RATE

Thirty (30) to forty (40) square meter per 4 liter on plain sanded surface. Give allowance for variable shaped metal members.

DRYING TIME

Fifteen (15) to thirty (30) minutes for completion of reaction. Drying time – same as plain water, depending on humidity.

MIXING INSTRUCTIONS

Shake the container before use.

PACKAGING

500 ml., 1 liter and 4 liter plastic containers

CAUTIONS

1. Store in shaded ventilated area.
2. Keep out of reach of children.
3. Keep tightly closed when not in use.
4. Acid. If it gets in contact with hands wash immediately with water. In eyes, wash immediately with water and see a doctor.
5. Do not ingest. If ingested, see a doctor immediately.
6. Do not inhale fumes.

(11/2/11)